



Part Number	HP	A	B	Weight (lbs)	C	D - Gas Thread	E	F	G	H	I	L	Mounting Holes
SPV 12 / SPV 18	0.12 / 0.18	255	90 T	6	165	3/4"	98	100	130	151	115	7	4
		285	120 T	7									
		335	170 T	7									
		385	220 T	7									
		435	270 T	7									
		515	350	8									
SPV 25 / SPV 33	0.25 / 0.33	300	90 T	10 / 11	210	3/4"	98	100	130	170	115	7	4
		330	120 T	10 / 11									
		380	170 T	10 / 11									
		430	220 T	10 / 11									
		480	270 T	11 / 12									
		560	350 T	11 / 12									
SPV 50 / SPV 75	0.50 / 0.75	460	200 T	17 / 20	260 (250*)	1 1/4"	138	140	180	215	160	9	4
		530	270 T	19 / 21									
		610	350 T	20 / 22									
		690*	440*	35 / 37									
		800*	550*	38 / 40									
SPV 100 / SPV 150	1.00 / 1.50	500	200 T	23 / 26	300	1 1/4"	138	140	180	230	160	9	4
		570	270 T	24 / 27									
		650	350	26 / 29									
		740*	440*	42 / 44									
		850*	550*	45 / 48									
IMM 90A / IMM 90B	2.00 / 3.00	695	350	105 / 109	345	2"	235	240	300	130	270	13	4
		795	450	107 / 110									
		945	600	108 / 111									
		1145	800	111 / 114									
IMM 100B	5.00	730	350	117	380	2 1/2"	235	240	300	145	270	13	4
		830	450	119									
		980	600	120									
		1180	800	123									

* Cast Iron

T = TRI mode for glass processing machinery